

# SPECIFICATIONS

## Ducted Cooling Units



# Sentinel Series

<b>Model Number</b>		<b>D025 (R134A)</b>
<b>Power Requirements</b>	volt/phase/hz	115/1/60
<b>Performance</b>		
Net Cooling Capacity*		Total/Sensible
@60 Deg F condenser inlet air	BTUH	4520/3050
@70 Deg F condenser inlet air	BTUH	4300/2915
@80 Deg F condenser inlet air	BTUH	3760/2715
@90 Deg F condenser inlet air	BTUH	3540/2580
@110 Deg F condenser inlet air	BTUH	3260/2400
@120 Deg F condenser inlet air	BTUH	3000/2260
<b>Controls</b>		
Type		Digital electronic
Temperature Accuracy/RH% Accuracy		1F / 10%
<b>Evaporator Section</b>		
Fan Motor Size	Watts	75
Rated Air Flow (free blow)	CFM	245
Rated Air Flow @ pressure loss	CFM	200 @0.10" wc
<b>Air-cooled Condenser Section</b>		
Fan Motor Size	Watts	75
Rated Air Flow (free blow)	CFM	245
Rated Air Flow @ pressure loss	CFM	200 @0.10" wc
<b>Water-cooled Condenser Section (option)</b>		
Water usage at 20 Deg F rise	GPM	0.50
Pressure drop	PSI	0.20
Pipe connection size (in/out) O.D.	Inches	0.50
<b>Heat (Option)</b>		
Type		Electric
Capacity	Watt/BTUH	1000/3400
<b>Humidifier (Option)</b>		
Type		Removable drip pad with integral fan
Capacity - water temp of 60 Deg F	lbs./hr	0.42
Capacity - water temp of 90 Deg F	lbs./hr	0.97
Capacity - water temp of 100 Deg F	lbs./hr	1.11
<b>Electrical Requirements</b>		
Current Draw - Cooling mode	Amps	7.1
Current Draw - Heating mode	Amps	9.4
Minimum Circuit amps (heat / no heat)	Amps	11.6/8.6
Optional Low Ambient	Amps	0.4
Optional High Ambient	Amps	0.2
Optional Humidifier	Amps	0.4
<b>Cabinet</b>		
Construction		Aluminum chassis & UL Rated plastic panels
Finish		Gray Metal epoxy powder coat/textured PVC Acrylic blend
Weight	lbs.	78
Dimensions (inches)	Width	33.45
	Depth	16.6
	Height	15.56
<b>Condensate Drain connection (ID)</b>	inches	.50"
<b>Agency approval</b>	ETLc	UL 1995 / CSA C22.2

1. Net cooling capacity at entering temperature and humidity conditions of 57 Deg F and 55% RH at rated airflow. Reduce capacity by 3% for each 10% reduction in evaporator airflow.
2. Wine Guardian reserves the right to make changes to this document without prior notice at its sole discretion.
3. All rating at sea level.

Wine Guardian Factory & Headquarters:  
7000 Performance Drive | North Syracuse, New York 13212 USA

Wine Guardian European Office:  
Pestalozzistrasse 2, CH-8201 Schaffhausen, Switzerland

help.wineguardian.com | info@wineguardian.com  
Wine Guardian® is a registered trademark of Air Innovations